Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LED-Fluter Plug & Light

Supplier's address: Albrecht JUNG GmbH & Co. KG, Zentrale, Volmestraße 1, 58579 Schalksmühle,

DE

Model identifier: PLF1D05WW

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	DLS
Light source cap-type	Nein		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	250 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 800		
On-mode power (P _{on}), expressed in W	4,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,03		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	95		

Outer	Height	70	Spectral power	See image	
dimensions	Width	70	distribution in the	in last page	
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	23	range 250 nm to 800 nm, at full-load		
Claim of equival	lent power ^(a)	-	If yes, equivalent power (W)	-	
			Chromaticity	0,450	
			coordinates (x and y)	0,402	
Parameters for	directional light	sources:			
Peak luminous i	ntensity (cd)	794	Beam angle in degrees, or the range of beam angles that can be set	37100	
Parameters for LED and OLED light sources:					
R9 colour rende	ering index value	73	Survival factor	0,99	
the lumen main	tenance factor	0,96			

(a)'-': not applicable;

(b)_{'-'} : not applicable;

